

**Materialprüfungsamt Nordrhein-Westfalen**

Prüfen • Überwachen • Zertifizieren

**Certificate of conformity of the factory production control****0432-CPR-00375-20 (EN)**

Version 03

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

**double-wall system chimney**with 35 mm heat insulation (96 kg/m<sup>3</sup>)

and flue liners made of stainless steel: 1.4404 / 14571

**"ThermoVast DWH-DWBA"***(for a detailed product description see annex 1 of this certificate)*

placed on the market under the name or trade mark of

**Thermo Products B.V.**

Bedrijfsweg 14

4387 PD Vlissingen, Netherlands

and produced in the manufacturing plant(s)

**Thermo Products B.V.**

Bedrijfsweg 14

4387 PD Vlissingen, Netherlands

and produced in the manufacturing plant(s)

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

**EN 1856-1:2009-06**under **system 2+** are applied and that

**the factory production control is assessed to be in conformity with the applicable requirements**

This certificate was first issued on 01.04.2017 and will remain valid until 15.04.2019 as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Dortmund, 16.04.2018

*by order**Hönig*

Dipl.-Ing. Hönig

Head of Certification Body (Dept. 21)

This Certificate consists of 1 page and 1 annex(es).

This Certificate replaces the Certificate no. 0432-CPR-00375-20  
dated 13.04.2017, Version 02.

The original of this document was issued in German language.  
In case of doubt only the German version is valid.



## Declared conditions by the manufacturer for "ThermoVast DWH-DWBA"

	type of chimney/ flue pipe	standard	Product description
01	"ThermoVast DWH-DWBA" double-wall system chimney with heat insulation  inner pipe: 1.4404 / 1.4571 wall thickness: 0,4 mm (-10 %) (DN80-250) 0,5 mm (-10%) (DN300-600) insulation: 35 mm; 96 kg/m <sup>3</sup> outer pipe: 1.4301 wall thickness: 0,5 mm; 0,6 mm	EN 1856-1:2009	T600 – N1 – D – Vm – L50040/50 – G(75) (DN 80-300) T600 – N1 – D – Vm – L50050 – G(112.5) (DN 350-450) T600 – N1 – D – Vm – L50050 – G(150) (DN 500-600)  DN 80/150-600/670